



Rev.	ECO#	Date	Ву	
C	0195-0612	06/21/2012	MWP	


2.5	Nx3.81
	





Material: Contact Solder Pin: Brass, Tin Plated Wire Guard: Steel, Zinc Plated M2, Steel, Zinc Plated, "-" slotted Insulating Body: | Polyamide, UL94V-0 Electrical Voltage Rating: 300 VAC Current rating: 8 AMPS Withstand Voltage: 1500 VAC, Test time 60 sec Wire Range: 16-26 AWG Mechanical Torque: 2.0 Lbs-in. Max -40°C to +115°C Operating Temperature: -40°F to +239°F Soldering Temperature: 260°C, 500°F for 5 seconds c**M**us Safety Approval:

N=Number of Positions



P.C.B. Layout

Part Number Configuration. EB2215-XXDS-500

Number of Positions 5-Green

/Other Color Options Available\ Please consult Factory

Max Number of Positions = 24

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES

3.81mm SPACING, WIRE GUARD BLOCK

LIMITS: UNLESS SCALE THIS IS A CONFIDENTIAL DRAWING AND OTHERWISED SPECIFIED MUSTBE TREATED AS SUCH. NO HUND.±.02 FRACT.±1/64 DISTRIBUTION IS ALLOWED WITHOUT THOU.±.005 ANGLE±1° WRITTEN APPROVAL BY EBY ELECTRO INC

Electro Inc. PLAINVIEW, NY 11803

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples | METRIC LIMITS and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

DATE 12/29/08 DRAWN CHECKED DATE **APPROVED** DATE

EB2215-XXDS-500