





RoHS Compliant

Rev.	ECO#	Date	By
A	0286-0313	03/14/13	AJT



Material:	
Contact Clip:	PhBz, Tin Plated
Wire Retention Spring:	Stainless Steel
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	160 VAC
Current rating:	5.5 AMPS
Withstand Voltage:	1300 VAC, Test time 60 sec
Wire Range:	16-24 AWG
Mechanical	
Operating Temperature:	-40°C to +105°C -40°F to +221°F
Safety Approval:	US

N=Number of Positions



Part Number Configuration.

EB445-XX-500
 | |
 Number of Color
 Positions 5-Green

(Other Color Options Available)
 Please consult Factory

Max Number of Positions = 24

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE:	SCREWLESS PLUGGABLE BLOCK 3.50mm SPACING	
	LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EB445 ELECTRO INC.
DRAWN <u> JM </u> DATE <u> 10/08/08 </u> CHECKED _____ DATE _____ APPROVED _____ DATE _____		SIZE	DRAWING NUMBER:
		A	EB445-XX-500
		PLAINVIEW, NY 11803	

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EB445 Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ± 1°	REV.	A
---	------	---