




RoHS Compliant

Rev.	ECO#	Date	By
D	0416-0413	04/02/13	AJT

N=Number of Contacts



Material:	
Contact Solder Pin:	Brass, Tin Plated
Wire Retention Spring:	Stainless Steel
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating:	10 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	12-28 AWG
Mechanical	
Operating Temperature:	-40°C to +105°C -40°F to +221°F
Soldering Temperature:	260°C, 500°F for 5 seconds
Safety Approval:	US



PCB Layout

Part Number Configuration.

EB490-XX-803
 | |
 Number of Color
 Positions 8-Grey

(Other Color Options Available)
 Please consult Factory

MAX NUMBER OF POSITIONS = (3x12) = 36

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE:	10.16mm SPACING, SCREWLESS BLOCK	
	LIMITS: UNLESS OTHERWISE SPECIFIED HUND. ± 0.2 FRACT. ± 1/64 THOU. ± 0.05 ANGLE ± 1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUST BE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EB490 ELECTRO INC.
DRAWN <u> JM </u> DATE <u> 08/02/07 </u>		SIZE	DRAWING NUMBER:
CHECKED _____ DATE _____		<u> A </u>	<u> EB490-XX-803 </u>
APPROVED _____ DATE _____			PLAINVIEW, NY 11803

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EB490 Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ± 0.3 TWO PLACES ± 0.10 ANGLE ± 1°	REV. <u> D </u>
---	-------------------