



Material:	
Contact:	Brass (CuZn), Nickel Plated
Wire Guard:	PhBz, Tin Plated
Screw:	M2.6, Steel, Zinc Plated
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating:	10 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	14-26 AWG
Mechanical	
Torque:	3.5 lbs-in. Max
Operating Temperature:	-40°C to +115°C -40°F to +239°F
Safety Approval:	CE US

### Part Number Configuration

EB550-XXDS-XX0

Number of Positions	Color Option:	Screw Option:
	0- Black	0- Slotted, "-"
	2- Red (RAL 3001/D)	3- Phil-slot, "+"
	8- Gray (RAL 7004/P)	

Notes:  
1-Mates with a φ1.0mm pin

MAX NUMBER OF POSITIONS = 24

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE: 5.00mm SPACING, PLUGGABLE BLOCK 2-FINGER CONTACT CLIP, CHASSIS MOUNT
---	---

LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±0.2 FRACT.±1/64 THOU.±0.05 ANGLE±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EB5 ELECTRO INC.	Electro Inc. PLAINVIEW, NY 11803
--	-------	--	-------------------------------------