




RoHS Compliant

Rev.	ECO#	Date	By
E	0149-0112	01/26/2012	MWP



Material:	
Contact Block:	Brass, Ni Plated
Contact Solder Pin:	Brass, Tin Plated
Screw:	M2.5, Steel, Zinc Plated, "-" slotted
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating:	10 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	12-22 AWG
Mechanical	
Torque:	3.5 lbs-in. Max
Operating Temperature:	-40°C to +115°C -40°F to +239°F
Soldering Temperature:	260°C, 500°F for 5 seconds
Safety Approval:	C <sub>RU</sub> US



N=Number of Positions


Part Number Configuration.

EB762-XX-500

Number of Positions: 5  
Color Option: Green

(Other Color Options Available)  
Please consult Factory

Max Number of Positions = 16



P.C.B. Layout

TITLE: 7.62mm SPACING, CAGE CLAMP BLOCK STACKABLE w/ DOVE TAILS

LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.		
	DRAWN: MWP CHECKED: _____ APPROVED: _____			DATE: 06/03/04 DATE: _____ DATE: _____

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ±1°	DRAWN: MWP CHECKED: _____ APPROVED: _____	DATE: 06/03/04 DATE: _____ DATE: _____	SIZE: A	DRAWING NUMBER: EB762-XX-500	REV.: E
--	---	--	---------	------------------------------	---------