





RoHS Compliant

Rev.	ECO#	Date	By
E	1431-0121	01/13/212	MWP



Material:	
Clamping Cam:	Steel, Zinc Plated
Contact Clip:	PhBz, Tin Plated
Screw:	M3, Steel Zinc Plated, "-" Slotted
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating:	20 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	12-22 AWG
Mechanical	
Torque:	3.5 Lbs-in. Max
Operating Temperature:	-40°C to +105°C -40°F to +221°F
Safety Approval:	UL US




Part Number Configuration.

EB1560M-XX-500

Number of Positions: 5
Color: 5-Green


(Other Color Options Available)
Please consult Factory



Max Number of Positions = 24

TITLE: 5.00m SPACING, PLUGGABLE BLOCK WIRE ENTRY ON TOP, MOUNTABLE

LIMITS: UNLESS OTHERWISE SPECIFIED ONE PLACE ±0.3 HUND. ±0.2 THOU. ±0.05	FRACT. ±1/64 ANGLE ±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUST BE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EB1560M-XX-500	EBY Electro Inc. PLAINVIEW, NY 11803
---	---------------------------	-------	---	--



IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EB1560M-XX-500 Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS	DRAWN	DATE	SIZE	DRAWING NUMBER:	REV.
ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ±1°	MWP	02/25/03	A	EB1560M-XX-500	E
	CHECKED	DATE			
	APPROVED	DATE			